

Open Frame LCD

Open Frame LCD




6.5"(4:3)

Specifications



| | |
|--------------------------------|---|
| Model Name | R06L200-OFA1 |
| Panel Size | 6.5" |
| Active Display Area(mm) | 132.48 (H) x 99.36 (V) |
| Resolution | 640 x 480 |
| Brightness(cd/m2) | 700 (Typical) |
| Contrast Ratio | 600:1 (Typical) |
| Viewing Angles(CR>=10 L/R/U/D) | -80~80(H) ; -70~70(V) |
| Display Colors | 262K (6 bits/color) |
| Standard Input Signal | 1 x VGA (D-sub 15) 1 x HDMI (Type-A) |
| Touch Screen(Optional-1) | Resistive Touch Protective Glass |
| Touch Interface | USB / RS232 |
| Audio / Speakers (Optional)* | Audio line in (3.5mm) + Speaker x2 |
| OSD | 5 Keys: -, +, Power, Esc, Enter |
| Power Input | 12V DC input (2.5ψ) with external AC-DC Adapter (100V~240V) |
| Power Consumption | 15W typical, Normal operation |
| Operating temperature | 0~50°C |
| Storage Temperature | -10~60°C |
| Accessories | Power AC-DC Adapter(100V~240V) VGA cable (1.8m) HDMI cable (2m) |

*Outside dimension and I/O will be different from standard




1. VGA
2. HDMI
3. DC input

I/O Optional

| | |
|-------------|--|
| Optional 1* | 1 x VGA (D-sub 15) 1 x S-Video 1 x Composite |
|-------------|--|

Mechanical Drawing



* Note: The mechanical drawing may change when adding touch screen. Please contact our sales representative if you need further product information.