


Rugged Panel PC



Model:W12IB3S-VMM9

Product Features:


- Ultra Low Bay Trail N2930 1.83GHz Processor Fanless Design
- 5 Wire resistive touch screen
- -10 ~ +55°C Wide Range Operating Temperature
- Anti-Corrosion housing with Fanless Design
- 9V ~ 36V DC Isolation Wide Range Power (default)
- Anti-Shock & Vibration compliant with MIL-STD-810F/G
- Optional 6-60V DC Input, and Optional for Ignition On/Off delay
- Panel Mount for request
- Design to meet EN50155



Product Specifications:


Display	Model Name	W12IB3S-VMM9	
	Size	12.1"	
	Resolution (pixels)	1280 x 800	
	Number of Colors	262.144 (6bits/color)	
	Brightness (cd/m2)	400	
	Contrast Ratio	1000 :1	
	Viewing Angle	-88~88 (H) ; -88~88 (V)	
	Active Area	261.12 (H) x 163.2 (V)	
	Touch (optional)	5 wire resistive	
	System	Processor	Intel® Bay Trail N2930 1.83Ghz Processor
Chipset		Bay Trail SoC Chipset	
BIOS		AMI 16Mbit Flash	
Memory		1xDDR3L 1600 MHz SO-DIMM, default 4GB, Max. 8GB	
Ethernet		Intel® I210-AT GbE LAN	
Input/Output	Storage	mSATA SSD, default 64GB	
	1 x USB 3.0, 1 x USB 2.0		
	1 x HDMI		
	1 x RS-232		
	1 x RS-232/422/485		
	1 x DC-IN Terminal Block		
	1 x WLAN or 3G Antenna in top (optional)		
	Environment	Operating Temperature	-10 ~55°C
		Storage Temperature	-30 ~70°C
		Humidity	10 ~ 95% non-condensing
Shock		MIL-STD-810F/G	
Vibration		MIL-STD-810F/G	
Power Input	Power Input	9~36V DC in with isolation (Phoenix type)	
	Safety	Optional 6-60V DC in, with Ignition On/Off delay	
Driver OS Support	Safety	MIL-STD-810F/G	
	Windows Embedded Standard 7 (64-bit)		
	Windows Embedded 8.1 Industry Pro 64-bit		
Mechanical	Windows 10 IoT Enterprise		
	Dimension(W x H x D)	310 x 215 x 52.7 mm	
Packing List	Approximate Weight	2.8 kg*	
		*Weight of this device will be more or less depending upon actual component configuration	
Security Support	Packing List	(IB32) SBC Manual & Driver CD	
		Trusted Platform Module (TPM 1.2)	

I / O View:



1. RS232
2. RS232/422/485
3. 1xUSB 2.0, 1xUSB 3.0
4. HDMI
5. 2xRJ45
6. Terminal Block 9~36V

Rear OSD Control Function:



Drawing w/o Mounting bracket:

