

# 10.4" Vehicle Mounted Computer

FM10

## Product Features:

- Field replaceable front panel to reduce service cost and prevent productivity loss
- High Performance Intel ATOM platform (E3845 2M Cache, 1.91GHz)
- Support Windows 10 IoT Enterprise, Windows Embedded 8.1 Industry Pro, Windows 7 Professional for Embedded system, or Windows Embedded Standard 7
- Magnesium Alloy Housing
- Anti-scratch resistive touch
- SMA Connector for external antenna
- Fan-Less & Robust Design
- Wide range Operating Temperature
- Carrier Approval: PTCRB, AT&T



FM10

FM10C (Computer)

FMVD (Dock)

## Product Specifications:

System Specification	Processor	Intel Quad-Core Atom E3845 Processors (1.91GHz)
	System Memory	4GB SODIMM DDR3L-1600 (up to 8GB)
	Storage	64GB M.2 MLC SSD (up to 256 GB)
Operating System	Operating System	Windows 10 IoT Enterprise Windows Embedded 8.1 Industry Pro Windows 7 Professional for Embedded system Windows Embedded Standard 7
	Size / Technology	10.4" (4:3)
	Resolution	1024*768
	Viewing angle	-88~88(H) ; -88~88(V)
Display Specification	Brightness	400 nits
	Touch	Anti scratch Resistive touch and support for finger touch and stylus
	WLAN	802.11 a/b/g/n/ac
	Bluetooth	Bluetooth 4.0
Wireless Communication	GPS	Optional u-blox NEO-6Q (located at the vehicle dock)
	WWAN	Optional 4G (LTE,HSPA+,GSM/GPRS/EDGE,EV-DO Rev A, 1xRTT) Optional 3G (HSPA+,GSM/GPRS/EDGE)
	Carrier Approval	PTCRB, AT&T
	Data Capture	Camera
Mechanical and Environment	Dimension (W x L x H)	Computer: 268 x 214 x 35 mm (10.6" x 8.42" x 1.37") Docking: 202 x 245 x 52 mm (7.9" x 9.6" x 2.04")
	Housing	Magnesium Alloy housing with fanless design
	Weight	Computer 1.7kg and Docking 1.6kg
	Operating Temperature	-30°C to 50°C (-22° to 122° F)
	Storage Temperature	-30°C to 60°C (-22° to 140°F)
	Humidity	5% to 95% RH, non-condensing
	IP Proof	IP65
	Impact	Support EN62262 IK70 rating
	Shock	Compliant with MIL-STD-810G Method 516.6 Procedure I
	Vibration	Compliant with MIL-STD-810G Method 514.6 Procedure I
I/O Connectors	Computer	1 x SIM Card Slot , 1 x SD Card Slot , 1 x USB 3.0, 1 x 12V DC in power input jack 1 x COM 1, 1 x COM 2, 1 x USB 2.0 port (support 2 x USB 2.0), 1 x CANBUS / AUDIO, 1 x 400Mbps LAN port (Optional PoE) as a Power sourcing equipment (PSE) support 802.3at Type 2, 1 x Power Connector, SMA Connector(female) for external antenna (WiFi, GPS, WWAN(optional))
	Dock	
Mobile Device Management	Mobile Device Management	SOTI MobiControl compatible
Power Management	Power Input	10V-60V with isolation power and ignition control
	UPS Battery	7.6V typ. 3800mAh Li-Polymer Battery (2S1P)

## Renderings :



# 10.4" Vehicle Mounted Computer

FM10

## Docking Features:

- Wide range power (10V~60V) & Ignition control
- Smart Docking Design
- u-blox NEO-6Q GPS (Optional)
- High power speaker (3W \* 2)
- With LED Reading Light
- Release latch and Key Lock to secure the device
- Power switch, to give power to the device
- VESA 75, 100, and RAM Mount



## FM10 – Accessories

### Package Contents

Before using this Vehicle Mounted Computer, please make sure that all the items listed below are present in your package:

Computer - FM10 <b>98P010A000J7</b>	Dock + latch locking key <b>98D000A00003</b>	5 m Power Cable with fuse kit <b>98K000A0006O</b>	0.3 m USB Cable <b>9483098080K0</b>	External Antenna Fixing Bracket <b>88111T201203</b>	Cable Clamp Kit <b>98K000A0005W</b>
WiFi External Antenna x 2 <b>39700000000G</b>	Quick Start Guide <b>9152111100S</b>	Driver CD <b>9171111101R</b>	0.15m power converter cable <b>94J602G030K2</b>	84W Adapter with power cable <b>922D084W12V1</b>	

## Optional Accessories

3 m DC Jack Power Cable <b>94J0086020K0</b>	1.2 M 120 Watt Adapter (For Heater Model) <b>90PO12120005</b>	4.2 m Adapter with power cable <b>98K000A0006L</b>	1.8 m RS232 Cable <b>94G3094090K2</b>	0.3 m Audio Cable <b>94E215R060K0</b>	1.8 m CAN BUS Y Cable <b>94E2150090K0</b>
2 m IP65 LAN Cable <b>94I0080080KF</b>	WWAN External Antenna x 2 <b>39700000000H</b>	15A, 250V, VDA type Fuses <b>94JL01L01000</b>	Spare Key for Vehicle Dock <b>9B000000007N</b>	DC12V/2A Input UHF Fixed Reader <b>9BRFID000012</b>	Mounting kit 1 – No Drill <b>98K000A0005Y</b>
Mounting kit 2 – Drill <b>98K000A0006P</b>	Mounting kit 3 – Keyboard Mounting <b>98K000A0005X</b>	GPS & LTE 2M Combo Antenna (VM240) <b>39700000000M</b>	GPS & LTE 5M Combo Antenna (VM9C) <b>39700000000N</b>	GPS & LTE & Wi-Fi Magnetic Combo Antenna (VM10S) <b>39700000000U</b>	Stylus kit + Screw <b>98K000A0005T</b>